

**TIMING BELT SELECTION CHART..... 16**

**NEOPRENE TIMING BELTS**

MXL – .080" Pitch.....	17
XL – 1/5" Pitch.....	20
L – 3/8" Pitch .....	22
HTD® – 3 mm Pitch .....	24
HTD® – 5 mm Pitch .....	26
GT®2 – 2 mm Pitch.....	28
GT®2 – 3 mm Pitch, Single- & Double-Sided .....	30
GT®2 – 5 mm Pitch, Single- & Double-Sided .....	34

**TruMotion® TIMING BELTS**

Specifications .....	60
MXL – .080" Pitch.....	36
XL – 1/5" Pitch.....	38
L – 3/8" Pitch .....	40
GT®2 – 2 mm Pitch .....	41
GT®2 – 3 mm Pitch.....	42
GT®2 – 5 mm Pitch.....	43

**TIMING BELT CLAMPS**

MXL, XL, GT®2 – 2 mm Pitch, HTD® & GT®2 – 3 & 5 mm Pitches, Polycarbonate....	44
XL & L – 1/5" & 3/8" Pitches Aluminum .....	45
HTD® – 5 & 8 mm Pitches, Aluminum .....	46
GT®2 – 2 & 3 mm Pitches, Aluminum.....	47
GT®2 – 5 & 8 mm Pitches, Aluminum.....	48
AT – 5 & 10 mm Pitches, Aluminum.....	49
T – 5 & 10 mm Pitches, Aluminum .....	50

**TIMING BELT PULLEYS**

L – 3/8" Pitch, Steel.....	51
HTD® – 8 mm Pitch, Nylon with Aluminum Insert.....	52
GT®2 – 2 mm Pitch, Polycarbonate.....	54
GT®2 – 3 mm Pitch, Polycarbonate.....	55

**LADDER CHAIN, SPROCKETS AND POSI-DRIVE BELTS**

Ladder Chain & Sprockets – .185" (4.7 mm) Pitch, Acetal with Metal Insert.....	56
Ladder Chain & Sprockets – .353" (8.9 mm) Pitch, Acetal with Metal Insert.....	57
Posi-Drive Belts – 32 Pitch (CP 2.5 mm).....	59